

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number
WO 2005/071780 A1

(51) International Patent Classification⁷: **H01M 8/02**,
8/10, 8/24

(21) International Application Number:
PCT/JP2005/001314

(22) International Filing Date: 25 January 2005 (25.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-018878 27 January 2004 (27.01.2004) JP

(71) Applicant (for all designated States except US): CANON
KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko,
Ohta-ku, Tokyo 1468501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MOGI, Satoshi

[JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2,
Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). SHIBATA,
Masaaki [JP/JP]; c/o CANON KABUSHIKI KAISHA,
3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).


(74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3,
Marunouchi 3-chome, Chiyoda-ku, Tokyo 1000005 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: FUEL CELL UNIT



(57) Abstract: A fuel cell unit is provided which comprises at least one structural member, the structural member comprising two electrolyte/electrode bonded members (14) each comprising a first electrode (13) and a second electrode (12) and an electrolyte membrane (11) disposed between the electrodes, a conductive porous substrate (15) disposed between the two electrolyte/electrode bonded members (14) so as to be in contact with the two first electrodes (13) of the two electrolyte/electrode bonded members, a conductive support member (18) provided on the porous substrate (15) so as to be electrically connected to the porous substrate (15) and the two first electrodes (13), and an electrical connection means (16) for electrically connecting the two second electrodes (12) being not in contact with the porous substrate of the electrolyte/electrode bonded members, and which attains size reduction, has as less wiring as possible, and gives a large electromotive force.

WO 2005/071780 A1